

IoT Wireless Temperature, Relative Humidity, CO2 and atmospheric pressure Datalogger with built-in 2G modem and Flat Rate SIM Card

Art nr: U4440Msim



IoT Wireless Datalogger kit with built-in GSM modem and Flat Rate SIM Card allows the instant connection to the COMET Cloud. IoT Datalogger is designed to record temperature, humidity, atmospheric pressure and CO2 from built-in sensors. In case of exceeded set limits e-mail is sent from the [COMET Cloud](#).

Alarms are also indicated locally by LED, LCD and acoustically by built-in beeper.

The recording is performed in a non-volatile electronic memory. The data can be transferred to a PC via included USB-C cable.

GSM recorder **includes Traceable calibration certificate** with declared metrological traceability of etalons is based on requirements of **EN ISO/IEC 17025 standard**.

Tekniska specifikationer

TEMPERATURGIVARE	
Mätområde	-20 till +60 °C
Noggrannhet	±0.4 °C
Upplösning	0.1 °C
LUFTFUKTIGHETSGIVARE	
Mätområde	0 till 100 % RH
Noggrannhet	± 1.8 % RH
Upplösning	0.1% RH
DAGGPUNKT	
Mätområde	-60 till +60 °C
Noggrannhet	±1.5 °C vid T <25 °C och RH >30 %
Upplösning	0.1 °C
CO2-GIVARE	
Mätområde	0 till 5000 ppm
Noggrannhet	±(50ppm +3% av avläst värde) vid 25°C och 1013hPa
Upplösning	1 ppm
BAROMETERTRYCKSGIVARE	
Mätområde	700 till 1100 hPa
Noggrannhet	±1.3 hPa vid 23 °C från 800 till 1100 hPa
Upplösning	0.1 hPa
TEKNISKA SPECIFIKATIONER	
Drifttemperatur	-20 till +60 °C
Kanaler	interna givare för temperatur, luftfuktighet, CO ₂ & barometertryck
Minneskapacitet	500 000 värden i ickecykliskt läge (noncyclic logging mode), 350 000 värden i cykliskt läge (cyclic mode)
Loggningsintervall	justerbart 1s till 24h
Uppdatering display och larm	justerbart 1 s, 10s, 1min

Dataloggningslägen	Icke-cykliskt (non-cyclic): dataloggning avslutas när minnet är fullt, cykliskt (cyclic): när minnet är fullt skrivs det äldsta värdet över av det nya
Realtidsklocka	år, skottår, månad, dag, timme, minut, sekund
Matning	Li-Ion batteri A8200, 3,6V/5200mAh
Kapslingsklass	IP20
Dimensioner	61 x 93 x 53 mm, med antenn 120 x 93 x 53 mm
Vikt inkl. batteri	ca 250 g
Garanti	3 år